

## 22" Linear LED Bath

 Wall mounted • Damp location listed 

### P300150-150-30

#### Description:

LED bath and vanity fixtures in the Blanco collection highlight a classic form with contemporary updates. Brushed Nickel accents complement a Faux White Marble frame and canopy with a design that minimizes all visible hardware for an elegantly modern effect. Suitable for residential and commercial applications, fixtures can be installed vertically or horizontally to complement Modern, Luxe or Mid-Century interiors.

#### Specifications:

- Faux White Marble (-150) (Painted)
- Steel construction
- Etched White Glass Cylindrical
- LED sconces in the Blanco collection highlight a cylindrical design paired with a square faux marble back plate
- 1-light 35-watt LED bath fixture
- Blanco LED adds task lighting on either side or above a mirror to eliminate shadows on face when getting ready in the morning
- An integrated LED source provides a variety of energy and cost savings benefits for the homeowner
- Features Brushed Nickel end caps
- Measures 22 1/4"W x 4 3/4" H
- 53.8 lumens per watt
- Details highlight clean construction with no visible hardware
- Blanco is suitable for both residential and commercial bathroom spaces
- Can be installed vertically or horizontally to accommodate Modern, Luxe or Mid-Century applications
- Warm white 3000K lighting color, 1940 lumens and 90+CRI
- Damp location listed
- Dimmable to 10% brightness (See Dimming Notes)
- Backplate covers a standard 4" octagonal recessed outlet box
- Mounting plate for outlet box included
- 6" of wire supplied
- Complies with "Americans with Disabilities Act" - ADA
- Meets California Title 24 JA8-2016

#### Performance:

|                     |                                     |
|---------------------|-------------------------------------|
| Number of Modules   | 1                                   |
| Input Power         | 35w                                 |
| Input Voltage       | 120 V                               |
| Input Frequency     | 60 Hz                               |
| Lumens/LPW          | 1940/53.8 (LM-79)                   |
| CCT                 | 3000 K                              |
| CRI                 | 90 CRI                              |
| Life (hours)        | (L70/TM-21)                         |
| FCC                 | Meets FCC Title 47, Part 15 Class B |
| Min. Start Temp     | -10 °C                              |
| Max. Operating Temp |                                     |
| Warranty            | 5-year limited warranty             |
| Labels              | cETLus Damp location listed         |
|                     | Meets California Title 24 JA8-2016  |

#### Images:



#### Dimensions:

Width: 22-1/4"  
 Depth: 3-5/8"  
 Height: 4-3/4"  
 H/CTR: 2-3/8"

Glass  
 Height: 2-3/8"

**P300150-150-30****Dimming Notes:**

---

P300150 is designed to be compatible with many Triac/ELV controls.

The following is a partial list of known compatible dimmer controls.

**Dimming Controls**

---

Lutron - NTELV-300

Lutron - DVELV-300P

Lutron - Caseta Wireless

Leviton – 6672

Leviton – 6674

Lutron - AYCL-153P

Lutron - AYLV-600P

Lutron - MAELV-601

Leviton - AWRMG-EAW

Lutron - N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.