

P350077 LED Flush Mount

Wall or Ceiling mounted • Damp location listed



Description:

LED flush mount with etched white opal acrylic diffuser with a clean modern look. 3000K color temperature and 90+ CRI. Acrylic bowl is attached with a twist and lock action for ease of installation. This fixture can be mounted on ceiling or wall. ENERGY STAR rated.

Specifications:

- Brushed Nickel (-009) (Plated)
- Steel construction Acrylic
- Etched white opal acrylic diffuser.
- Acrylic bowl is attached with a twist and lock action.
- Can be mounted on ceiling or wall.
- Dimmable to 10% with many ELV dimmers
- Acrylic diffuser twists into the frame so there are no exposed fasteners for a clean modern look.
- 2002 lumens, 77 lumen/watt
- 3000K color temperature, 90CRI
- covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified
- Meets California Title 24 JA8-2016

Performance:

Number of Modules	1
Input Power	26w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	2002/77 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	36,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30°C
Warranty	5 year warranty
Labels	UL Damp location listed
	ENERGY STAR® qualified
	Meets California Title 24 JA8-2016

P350077-009-30

Images:



Dimensions:

Diameter: 14"
Height: 4-3/4"

P350077-009-30

Dimming Notes:

P350077 is designed to be compatible with many Triac/Forward Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron NTEVL-3

Lutron DVELV-3 P

Lutron DVCL-253P

Lutron Caseta Wireless

Lutron AYCL-153P

Lutron TGCL-153-PH

Lutron NTLV-6

Lutron MAELV-6 1

Lutron N-6

Leviton 6674

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.