

Project:	
ixture Type:	
ocation:	
Contact:	

## MILFORD LED

Ceiling flush mounted. Damp location listed





### **Specifications:**

#### **Description:**

One-light LED flush mount with etched glass surrounded by a die-cast aluminum frame. Ideal for indoor and outdoor applications.

#### **Construction:**

- · Antique Bronze (-20) (painted)
- · Die-cast aluminum construction
- · Glass: Frosted Seeded glass bowl
- · LED Module is replaceable (Part # 93053641)
- Flicker-free dimming to 10% brightness with most ELV type dimmers (See Dimming Notes)
- · CA Title 24 compliant
- Ceiling pan covers a standard 4" hexagonal recessed outlet box
- · Mounting strap for outlet box included
- · 6" of wire supplied



P3665-2030K9

#### **Images:**



#### **Performance:**

Number of Modules	1
Input Power	17W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	1,211/71.2 (LM-79) per module
CCT	3000K
CRI	90
Life	60000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30
Max. Operating Temp	30
Warranty	5 year warranty
Labels	cCSAus Damp location listed
	ENERGY STAR® qualified

#### **Dimensions:**

Diameter: 8-5/8" Height: 4-1/8"

#### **Catalog number:**

Base		Finish		Color Temp			CRI	
P3665		20 - Antique Bronze	- •	<b>30K</b> - 3000K	_		9 - 90 CRI	



# MILFORD LED

Ceiling flush mounted · Damp location listed



### P3665-2030K9

#### **Dimming Notes:**

P3665 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

#### **Electronic Low Voltage ELV Reverse Phase Controls**

Lutron Diva Series (Part Number DVELV-300P)

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.