

roject:	
xture Type:	
ocation:	
ontact:	

DOME

Ceiling cord mount • Dry location listed





Specifications:

Description:

The simple design of this LED Dome pendant offers complements a wide array of styles from industrial to farmhouse. The 9w LED pendant is 3000K in an Antique Bronze finish with a painted gold interior.

Construction:

Antique Bronze (-20) (painted) Steel construction

LED Module is replaceable (part # 93054049)
Flicker-free dimming to 10% brightness with most ELV type dimmers
(See Dimming Notes)

Title 24 compliant

Canopy covers a standard 4" hexagonal recessed outlet box

Mounting strap for outlet box included

Ten feet of wire supplied

Performance:

Number of Modules	1			
Input Power	9W			
Input Voltage	120V			
Input Frequency	60Hz			
Lumens/LPW	623/69.2 (LM-79) per module			
CCT	3000K			
CRI	90+			
Life	60,000 (L70/TM-21)			
EMI/RFI	FCC Title 47, Part 15, Class B			
Min. Start Temp	-30° C			
Max. Operating Temp	30° C			
Warranty	5 year warranty			
Labels	cCSAus Dry location listed			
	ENERGY STAR® qualified			

P5340-2030K9

Images:



Dimensions:

Diameter: 10" Height: 5-5/8"

Overall ht. w/cord: 125-1/2"

Catalog number:

Base	Finish	(Color Temp	CRI
P5340	20 - Antique Bronze	3	30K - 3000K	9 - 90 CRI