

roject:		
ixture Type:		
ocation:		
ontact:		

DOME

Ceiling cord mount • Dry location listed





Specifications:

Description:

The simple design of this LED Dome pendant offers complements a wide array of styles from industrial to farmhouse. The 17w LED pendant is 3000K in a Satin Aluminum finish with a painted silver interior. This is an ideal fixture for residential and commercial applications.

Construction:

Satin Aluminum (-16) (powdercoat) Steel construction

LED Module is replaceable (part # 93053641)
Flicker-free dimming to 10% brightness with most ELV type dimmers
(See Dimming Notes)
Title 24 compliant

Canopy covers a standard 4" hexagonal recessed outlet box Mounting strap for outlet box included

Ten feet of wire supplied

Performance:

Number of Modules	1	
Input Power	17W	
Input Voltage	120V	
Input Frequency	60Hz	
Lumens/LPW	1211/71.2 (LM-79) per module	
CCT	3000K	
CRI	90+	
Life	60,000 (L70/TM-21)	
EMI/RFI	FCC Title 47, Part 15, Class B	
Min. Start Temp	-30° C	
Max. Operating Temp	30° C	
Warranty	5 year warranty	
Labels	cCSAus Dry location listed	
	ENERGY STAR® qualified	

P5341-1630K9

Images:



Dimensions:

Diameter: 16" Height: 8-7/8"

Overall ht. w/cord: 129"

Catalog number:

Base	Finish	Color Temp	CRI
P5341	16 - Satin Aluminum	30K - 3000K	9 - 90 CRI