

Project:		
Fixture Type:		
Location:		
Contact:		

# P550026 Hanging Lantern

Hanging mounted . Damp location listed PROGRESS LED





### **Description:**

Inspired by traditional lantern styles, Whitacre incorporates handsome details. Clear seeded glass surrounds an etched opal glass candle diffuser. An Antique Bronze finish complements a variety of exteriors, including Transitional and Traditional and Farmhouse designs.

#### **Specifications:**

- Antique Bronze (-020) (painted)
- AluminumClear Seeded with Etched Ivory diffuser Glass globe
- · Inspired by traditional lantern styles, Whitacre incorporates handsome details
- An Antique Bronze finish complements a variety of exteriors, including Transitional and Traditional and Farmhouse designs.
- Clear seeded glass surrounds an etched opal glass candle diffuser
- · Includes one 17-watt replaceable LED modules
- Warm white, 3000K, color temperature, 90 CRI
- · 1276 lumens, 73 lumens per watt
- Hanging lantern adds illumination to walkways and pathways to enhance safety and
- Replaceable light engine is California JA8 certified
- Dimmable with most Triac or ELV type dimmers
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- · 10 feet of wire supplied
- Six feet of 9 gauge chain supplied
- · ENERGY STAR® qualified
- Meets California Title 24 JA8-2016

#### **Performance:**

Number of Modules	1
Input Power	17w
Input Voltage	120 V
Input Frequency	
Lumens/LPW	1276/73 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30°C
Warranty	5 year limited warranty
Labels	cCSAus Damp location listed
	ENERGY STAR® qualified
	Meets California Title 24 JA8-2016

# P550026-020-30

#### Images:



#### **Dimensions:**

Diameter: 12-3/8" Height: 21"

Overall Ht. W/Chain: 96"

Glass Width: 7-7/8" Height: 12-5/8" Glass 2 Width: 4-3/4" Length: 4-3/4" Height: 4-3/4"



# P550026 Hanging Lantern

Hanging mounted • Damp location listed PROGRESS LED



P550026-020-30

### **Dimming Notes:**

P550026 is designed to be compatible with many Triac/ELV controls.

The following is a partial list of known compatible dimmer controls.

## **Dimming Controls**

Lutron Diva DVELV-300P

Lutron Nova T NTELV-300

Lutron Caseta

Lutron Ariadni AY-600P

Leviton Illumatech IPI06-1LZ

Lutron Lumea LG-603PG

Leviton SureSlide 6672

Leviton SureSlide 6674

Lutron Ariadni AYCL-153P

Lutron Skylark Contour CTCL-153P

Lutron Diva DVCL-153P

Pass & Seymour Harmony DCL453PTCCCV6

Lutron Toggler TGCL-153P

Lutron Maestro MACL-153M

Lutron Ariadni AYLV-600P

Lutron Maestro MA-600

Lutron NOVA T NTLV-600

lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Lutron Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.