

SECURITY

Backplate mount • Wet location listed



Specifications:

Description:

The 1000 Lumen LED swivel flood light has tempered glass and rugged die-cast construction. Order back plate (P6343) separately.

Construction:

Metallic Gray (-82) (powdercoat)
 Die-cast aluminum construction
 Tempered glass lens

Flicker-free dimming to 10% brightness with most ELV type dimmers
 (See Dimming Notes)
 Six inches of wire supplied

Performance:

Number of Modules	1
Input Power	13W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	1000/76.9 (LM-79) per module
CCT	3000K
CRI	90
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cCSAus Wet location listed

P6342-82/30K

Images:



Dimensions:

Diameter: 3-3/4"
 Height: 5"
 Depth: 3-1/4"

Catalog number:

Base	Finish	Color Temp
P6342	82 - Metallic Gray	30K - 3000K

P6342-82/30K

Dimming Notes:

P6342 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

Electronic Low Voltage ELV Reverse Phase Controls

Lutron	Diva Series	(Part Number DVELV-300P)
Lutron	Nova T Series	(Part Number NTELV-300)
Lutron	Vierti Series	(Part Number VTELV-600)
Lutron		(Part Number MAELV-600)
Lutron		(Part Number SPELV-600)
Leviton		(Part Number AWRMG-EAW)
Leviton		(Part Number 6615-P)

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.