

# DASH

Wall mounted • Damp location listed

## Specifications:

### Description:

The modern LED sconce is architecturally relevant, incorporating a creative design to shape light back on the wall for a dramatic effect. Perforated mesh is featured on the side to serve as diffusers. The brushed nickel finished is highlighted with polished chrome accents.

### Construction:

- Brushed Nickel (-09) (plated)
- Steel construction
- Glass: Acrylic
- LED Module is replaceable (Part # 93054049)
- Flicker-free dimming to 10% brightness with most ELV type dimmers (See Dimming Notes)
- CA Title 24 compliant
- Back plate covers a standard 4" hexagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied

### Performance:

Number of Modules	1
Input Power	9W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	623/69.2 (LM-79) per module
CCT	3000K
CRI	90
Life	60000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30
Max. Operating Temp	30
Warranty	5 year warranty
Labels	cCSAus Damp location listed ENERGY STAR® qualified

### Catalog number:

Base	Finish	Color Temp	CRI
P7163	09 - Brushed Nickel	30K -3000K	9 - 90 CRI

## P7163-0930K9

### Images:



### Dimensions:

Width: 4-1/2"  
 Height: 12-1/2"  
 Depth: 3-1/4"  
 H/CTR: 10-1/4"

**P7163-0930K9****Dimming Notes:**

---

P7163 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

**Electronic Low Voltage ELV Reverse Phase Controls**

---

Lutron	Diva Series	(Part Number DVELV-300P)
--------	-------------	--------------------------

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.  
Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.