

P730005 LED Flush Mount

Ceiling mounted • Damp location listed **PROGRESS LED**



Description:

LED flush mount with white acrylic diffuser mounts to baked enamel ceiling pan. Twist on installation with a single locking thumb screw. UL approved for damp locations. Ceiling or wall mount. 1680 lumens, 80 lumens/watt, 3000K and 90CRI. ENERGY STAR and Title 24.

Specifications:

- White (-030) (Painted)
- Steel construction Acrylic
- White acrylic diffuser
- Twist on installation.
- Wall or ceiling mount
- 1680 lumens, 80/lumens per watt
- 3000K color temperature, 90+ CRI
- Damp location listed
- Dimmable to 10% with many Forward Phase (Triac) or Electronic Low Voltage (ELV) dimmers
- covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified
- Meets California Title 24 JA8-2016

Performance:

Number of Modules	1
Input Power	21w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	1680/80 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	36,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30°C
Warranty	5 year warranty
Labels	ETL Damp location listed
	ENERGY STAR® qualified
	Meets California Title 24 JA8-2016

P730005-030-30

Images:



Dimensions:

Diameter: 11-1/8"

Height: 4-1/8"