

| Project:      |  |  |
|---------------|--|--|
| Fixture Type: |  |  |
| Location:     |  |  |
| Contact:      |  |  |

# Miter LED

Wall mounted • Damp location listed PROGRESS LED



# **Description:**

The Miter LED 24in linear bath bar highlights a beautiful layered effect to enhance a variety of interior areas. Each clear beveled glass panel is hand cut and positioned together, creating visual interest that extend to the corners. To complete the form, a back plate and linear accents frame the glass in a Brushed Nickel finish. Can be displayed horizontally or vertically. An integrated LED source provides a variety of energy and cost savings benefits.

## **Specifications:**

- Brushed Nickel (-009) (plated)
- Steel Construction
- Clear glass Beveled Panel, White glass diffuser
- · The clear beveled glass panel is in front of a cased white mitered glass shade
- · Linear accents frame the beveled glass
- · The LED light is diffused to create an even glow
- · The backplate and straps are finished in Brushed Nickel
- · Its fashion-forward style complements Modern and Traditional interiors
- Mount horizontally or vertically on the wall in bath and vanity settings to enhance a spa-like atmo-
- Measures 24in W x 5in ht.
- 36w integrated LED, 1,675 delivered lumens 54 lumens/watt, 3000K color temperature, 90+ CRI.
- · ETL Safety listed for use in damp locations
- · Compatible with many ELV dimmers
- Progress Lighting products are designed for exceptional quality, reliability, and functionality
- · Includes installation instructions and mounting hardware
- Coordinating fixtures available
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- 6" of wire supplied
- Complies with "Americans with Disabilities Act" ADA
- Meets California Title 24 JA8-2016

### Performance:

| Number of Modules      | 1                                  |  |
|------------------------|------------------------------------|--|
| Input Power            | 36w                                |  |
| Input Voltage          | 120 V                              |  |
| Input Frequency        | 60 Hz                              |  |
| Lumens/LPW (Source)    |                                    |  |
| Lumens/LPW (Delivered) | 1975/54 (LM-79)                    |  |
| ССТ                    | 3000 K                             |  |
| CRI                    | 90 CRI                             |  |
| Life (hours)           | 50,000 (L70/TM-21)                 |  |
| FCC                    | FCC Title 47, Part 15, Class B     |  |
| Min. Start Temp        | -30 ℃                              |  |
| Max. Operating Temp    | -30°C                              |  |
| Warranty               | 5-year limited warranty            |  |
| Labels                 | cETLus Damp location listed        |  |
|                        | Meets California Title 24 JA8-2016 |  |
|                        |                                    |  |



#### Images:



### **Dimensions:**

Width: 24" Depth: 3-7/8" Height: 5"

H/CTR: 2-1/2313" (horizontal)

Glass

Width: 24-1/16" Height: 4-5/8"



# Miter LED

Wall mounted • Damp location listed PROGRESS LED

P300152-009-30

# **Dimming Notes:**

is designed to be compatible with many Triac/ELV controls.

The following is a partial list of known compatible dimmer controls.

# **Dimming Controls**

Lutron - NTELV-300

Lutron - DVELV-300P

Lutron - Caseta Wireless

Leviton - 6672

Leviton - 6674

Lutron - AYCL-153P

Lutron - AYLV-600P

Lutron - MAELV-601 Leviton - AWRMG-EAW

Lutron - N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.