

Project:		
Fixture Type:		
Location:		
Contact:		

P300153-009-30

Miter LED

Wall mounted • Damp location listed PROGRESS LED

Description:

The Miter LED 34in linear bath bar highlights a beautiful layered effect to enhance a variety of interior areas. Each clear beveled glass panel is hand cut and positioned together, creating visual interest that extend to the corners. To complete the form, a back plate and linear accents frame the glass in a Brushed Nickel finish. Can be displayed horizontally or vertically. An integrated LED source provides a variety of energy and cost savings benefits.

Images:

Specifications:

- · Brushed Nickel (-009) (plated)
- Steel Construction
- · Clear glass Beveled Panel, White glass diffuser
- · The clear beveled glass panel is in front of a cased white mitered glass shade
- · Linear accents frame the beveled glass
- · The LED light is diffused to create an even glow.
- · The backplate and straps are finished in Brushed Nickel
- · Its fashion-forward style complements Modern and Traditional interiors
- Mount horizontally or vertically on the wall in bath and vanity settings to enhance a spa-like atmosphere
- Measures 34in W x 5in ht.
- 53w integrated LED, 2,825 delivered lumens 53 lumens/watt, 3000K color temperature, 90+ CRI.
- · ETL Safety listed for use in damp locations
- · Compatible with many ELV dimmers
- · Progress Lighting products are designed for exceptional quality, reliability, and functionality
- · Includes installation instructions and mounting hardware
- · Coordinating fixtures available
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- 6" of wire supplied
- Meets California Title 24 JA8-2016



Dimensions:

Width: 34" Depth: 3-7/8" Height: 5"

H/CTR: 2-1/2313" (horizontal)

Glass

Width: 34-1/8" Height: 4-5/8"

Performance:

Number of Modules	1	
Input Power	53w	
Input Voltage	120 V	
Input Frequency	60 Hz	
Lumens/LPW (Source)		
Lumens/LPW (Delivered)	2825/53 (LM-79)	
ССТ	3000 K	
CRI	90 CRI	
Life (hours)	50,000 (L70/TM-21)	
FCC	FCC Title 47, Part 15, Class B	
Min. Start Temp	-30 °C	
Max. Operating Temp	-30°C	
Warranty	5-year limited warranty	
Labels	cETLus Damp location listed	
	Meets California Title 24 JA8-2016	



Miter LED

Wall mounted • Damp location listed PROGRESS LED

P300153-009-30

Dimming Notes:

is designed to be compatible with many Triac/ELV controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron - NTELV-300

Lutron - DVELV-300P

Lutron - Caseta Wireless

Leviton – 6672

Leviton - 6674

Lutron - AYCL-153P

Lutron - AYLV-600P

Lutron - MAELV-601

Leviton - AWRMG-EAW

Lutron - N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.