

Rinnai offers Q-series (Combi/Heat Only wall-mounted) and QP-Series (All-in-One), condensing gas boilers that can be easily retro-fitted to replace traditional, less efficient boilers or provide simple, space-saving installation in new builds. All seven (Q&QP) models feature Rinnai's exclusive stainless steel heat exchanger to deliver unparalleled performance and efficiency.

## Rinnai Q Series Wall-Mounted Condensing Gas Boilers



- ~ ENERGY STAR® Qualified
- ~ Ultra Efficient Condensing Technology, Up to 95.4% AFUE
- ~ Stainless Steel Boiler Heat Exchanger
- ~ 6 gallon stainless steel charged indirect tank (Q175C)
- ~ Natural Gas and Propane Models Available
- ~ Limited 12 Year Heat Exchanger Warranty, 2 Years Parts, 1 Year Labor<sup>1)</sup>
- ~ Approved Venting: Polypropylene, Stainless Steel, PVC, CPVC
- ~ Ships with the following:
  - ~ Low Loss Header Plumbing Kit
  - ~ Fully Modulating Boiler Circulation pump
  - ~ Standard Concentric Venting and Two Pipe PVC Adaptor
  - ~ Wall Mounting Bracket

MODEL NO. <sup>2)</sup>	GAS TYPE	MIN/MAX INPUT BTU (HEATING)	MIN/MAX INPUT BTU (DIRECT HOT WATER)	MAX FLOW RATE DOMESTIC HOT WATER	AFUE	BOILER DIMENSIONS (W x H x D) <sup>3)</sup>	WEIGHT	HEADER DIMENSIONS (W x H x D)	WEIGHT <sup>4)</sup>	LIST PRICE
Q85SN	NG	17,000 / 85,000	Indirect tank compatible	Indirect tank compatible	95.4%	20+x 27+x 15+	110 lbs (50 kg)	16"x18"x6+	19 lbs (9 kg)	\$3,915
Q85SP	LP	37,000 / 85,000								\$3,915
Q130SN	NG	26,000 / 130,000	Indirect tank compatible	Indirect tank compatible	95.4%	20+x 27+x 15+	117 lbs (53 kg)	16"x18"x6+	19 lbs (9 kg)	\$4,250
Q130SP	LP	59,000 / 130,000								\$4,250
Q175SN	NG	35,000 / 175,000	Indirect tank compatible	Indirect tank compatible	95.0%	26+x 27+x 15+	141 lbs (64 kg)	20"x19"x6+	23 lbs (10 kg)	\$4,800
Q175SP	LP	74,000 / 175,000								\$4,800
Q175CN	NG	35,000 / 175,000	4.1 GPM (75° F Delta T)	4.1 GPM (75° F Delta T)	95.0%	40+x 27+x 15+	196 lbs (89 kg)	20"x19"x6+	23 lbs (10 kg)	\$5,800
Q175CP	LP	74,000 / 175,000								\$5,800
Q205SN	NG	41,000 / 205,000	Indirect tank compatible	Indirect tank compatible	95.0%	26+x 27+x 15+	141 lbs (64 kg)	20"x19"x6+	23 lbs (10 kg)	\$5,200
Q205SP	LP	74,000 / 205,000								\$5,200

## Rinnai Q Premier Gas Boilers



- ~ Ultra Efficient at 95.4% AFUE
- ~ Stainless Steel Boiler Heat Exchanger
- ~ Natural Gas (Propane Conversion Kits available)
- ~ 24-gallon stainless steel charged indirect tank
- ~ Modulating boiler pump
- ~ Fully-assembled system for easy installation
- ~ 5:1 turn down ratio
- ~ A complete solution - no sourcing components
- ~ Multiple plumbing and venting options for installation flexibility
- ~ Designed for zero-clearance installations
- ~ Approved Venting: Polypropylene, Stainless Steel, PVC, CPVC
- ~ Warranty: 12-year heat exchanger, 12-year tank, 2 year parts and 1-year labor\*\*
- ~ Integrated low loss header

MODEL NO. <sup>2)</sup>	GAS TYPE	MIN/MAX INPUT BTU	FIRST HOUR RATING (GALLONS)	AFUE	DIMENSIONS (W x H x D) <sup>3)</sup>	WEIGHT <sup>4)</sup>	LIST PRICE
QP85N	NG	17,000 / 85,000	141	95.4%	24+x 62+x 25+	236 lbs (107 kg)	\$6,300
QP130N	NG	26,000 / 130,000	211	95.4%	24+x 62+x 25+	243 lbs (110.2 kg)	\$6,500

NOTE:

1) Warranty may change depending on application and use. For complete warranty details, visit [www.rinnai.us/warranty](http://www.rinnai.us/warranty) or call 1-800-621-9419.

2) "C" in the model number is for "Combi", "S" is for "System" or "Solo", "QP" is for "Q Premier" All-in-One system

3) Boiler dimensions are only for the unit and shipping package not included.

4) Weight specification is for shipping weight.