Instinct Mirror IM0030CPFPDT Mirror Specification Sheet

FEATURES

- · Perimeter light pattern
- Integrated dimmable and tunable light controls
- Mirror defogging with auto-shutoff (45 minutes)
- Energy efficent, low profile LED lighting design
- Includes installation hardware

Kelvin	2700K - 5600K
CRI	90+
R9 Value	50+
Delivered Lumens	1522

ELECTRICAL FEATURES

- Electrical Enclosure (Power Supply) can be recess mounted behind mirror or remote/surface mounted
- Electrical enclosure includes standard 1/2" knockouts
- Operates on 120V 0.80A Max per Power Supply
- Total power use 56W (LED = 35W, Defogger = 21W)

CONSTRUCTION

- · Anodized aluminum back frame
- · Quality polished edge mirror
- · Constructed for surface mounting
- Includes aluminum electrical enclosure

DIMENSIONS


Width: 30" (762 mm)Height: 30" (762 mm)Depth: 7/8" (22.4 mm)

MORE INFORMATION




Scan the QR code to see the rough opening and electrical details found in the Instinct Mirror installation instructions.

Use the camera app on your mobile device to look at this QR code. This will allow you to quickly access web pages and other relevant documents.



Included Electrical Enclosure (Power Supply):



MODEL NUMBER KEY

PRODUCT LINE	WIDTH	<u>HEIGHT</u>	MIRROR SHAPE	LIGHT PATTERN	MIRROR FINISH	<u>OPTIONS</u>
IM	0	30	C = Circular	P = Perimeter	FP = Polished Edge	DT = Defogger, Tunable

OPTIONS

- Other widths / heights / shapes available
- Other light patterns available
- Remote power supply accessory available seperately: RPS-EXTEND15

CODES & STANDARDS


ETL certified to:

- UL 8750
- CSA Standard C22.2 No. 250.13

INSTALLATION OPTIONS

- · Mounts on wall surface with included hardware
- Electrical Enclosure (Power Supply) can be recess mounted behind mirror or remote/surface mounted

•



Front View Side View