



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11392 - 4.5 Watt MR16 LED; Silver Finish; 3000K; GU5.3 Base; 360 Lumens; 12 Volt



ELECTRICAL

Technology:	LED
Watts:	4.5W
Volts:	12V
Lumens:	360L
CRI:	80
CCT (Kelvins):	3000K
Temperature:	Soft White
Beam Spread :	40
Hours Rated:	25000
Dimmable:	Yes-Dimmable
DimmableText:	0-10V Dimming Only
Dimming Type :	Forward Phase or Reverse Phase
Incandescent Equivalent :	35W
Operating Temperature :	-25C (-13F) to +45C (+113F)
Number of LEDs :	6
Candlepower :	730
Power Factor :	0.94
Light Source:	LED
CBCP :	730
Warranty:	5 Year Limited - 10 hr per day

PACKAGING

Each UPC:	045923113925
Each Quantity:	1
Each Dimensions:	1.97 x 1.97 x 2.56
Inner UPC:	20045923113929
Inner Quantity:	12
Inner Dimensions:	6.42 x 4.33 x 5.51
Case UPC:	10045923113922
Case Quantity:	48
Case Dimensions:	13.70 x 9.45 x 6.50

PHYSICAL

ANSI Base:	GU5.3
Base:	Bi Pin GU5.3
Shape:	MR16
Finish:	Gray
Lens Finish:	Array
Lens Material:	Plastic
MOD (In.):	1.97
MOL (In.):	1.77
Weight (Lbs.):	0.08
Material:	Metal / Plastic / Electronic Components
Housing Color:	Gray
Lensed:	Lensed Lamp

COMPLIANCE

Safety Listing:	cULus
Location Rating:	Damp
Energy Star Qualified:	No
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S11392 - 4.5 Watt MR16 LED; Silver Finish; 3000K; GU5.3 Base; 360 Lumens; 12 Volt

DIMMER COMPATIBILITY

Lutron CTRP-253P

Lutron DVLV-600P

Lutron MA-PRO

Lutron NTLV-600

Lutron NTRP-250

Lutron SLV-600P
