

Ludington®

32" undermount single-bowl kitchen sink 32026

Features

- 36" minimum base cabinet width
- Single bowl
- 6" (152 mm) depth
- No faucet holes; requires wall- or counter-mount faucet
- Rear drain increases workspace in the sink and allows for more storage space underneath the sink
- Includes installation hardware
- Sink drain with strainer sold separately

Material

Premium 18-gauge stainless steel

Installation

Undermount

Recommended Products/Accessories


7400

K-23726 Drain treatment

K-23729 Stainless steel cleaner

Optional Products/Accessories

K-6644 Sink rack for Vault™ and Strive® kitchen sinks



ADA

Codes/Standards

ASME A112.19.3/CSA B45.4 ADA ICC/ANSI A117.1


STERLING® Stainless Steel Sinks Lifetime Limited Warranty


See website for detailed warranty information.




Ludington®


32" undermount single-bowl kitchen sink 32026





Recommended ADA Installation





Technical Information

All product dimensions are nominal.

Bowl configuration: Single

Installation:

Undermount

Min. base cabinet

36" (914 mm)

width:

Bowl area (Only):

Length: 30-1/4" (768 mm)

Width: 16-9/16" (420 mm) Bowl depth: 5-1/2" (140 mm) Water depth: 5-1/2" (140 mm)

Drain hole:

3-3/4" (94 mm)

Template:

Undermount, 1298947-7, required,

included

Notes

Install this product according to the installation instructions.

ADA compliant when installed to the specific requirements of these regulations.