

Single Control Faucet

TAG	

### **Architectural/Engineering Specification:**

Polished chrome plated cast brass 4" centerset single control lavatory faucet, a ceramic disc cartridge and a temperature limit stop. Unit is furnished with standard 2.2 GPM aerator, an ADA compliant lever handle, mounting hardware, 1/2" NPSM coupling nuts for standard lavatory risers, and pop-up hole plugged.

Zurn Lead Free products (-XL) is the line of durable, high quality brass faucets and fixtures that are designed and manufactured to comply with Section 1417 of the Safe Drinking Water Act (SDWA) which mandates the weighted average lead content of no more than 0.25% of the wetted surface.

#### **Product Features:**

- · Ceramic Disc Cartridge
- · Chrome-plated Cast Brass Body
- · ADA Compliant, Single Control Lever Handle
- 1/2" NPSM coupling nuts for standard lavatory risers

## **Compliance and Certification:**

- Low-Lead Compliant
- ADA Compliant



\*This device is WaterSense labeled when used with the appropriate flow rate and certified for residential and private restrooms.



# **Aerator Options:**

	Flow rate GPM [LpM]	Vandal Resistant	Pressure Compressation	*WaterSense Labeled	Outlet Type
-1 M	2.2[8.3]		✓		Aerator
-2M	2.2[8.3]	<b>✓</b>	✓		Aerator
-3M	0.5[1.9]	✓	✓		Spray
-4M	2.2[8.3]	✓	✓		Laminar
-5M	2.0[7.6]	<b>✓</b>	✓		Aerator
-7M	1.0[3.8]		✓	<b>✓</b>	Spray
-16M	1.0[3.8]	<b>✓</b>	✓		Spray
-17M	1.5[5.7]	<b>✓</b>	✓	<b>✓</b>	Aerator
-18M	1.5[5.7]	<b>✓</b>	✓	<b>✓</b>	Laminar
-22M	1.0[3.8]	<b>✓</b>			Laminar
-25M	0.35[1.3]	<b>✓</b>	✓		Spray
-28M	0.5[1.9]	✓			Laminar

## **Suffix Options:**

-G 1-1/4" [32mm] Grid Strainer Drain -P 1-1/4" [32mm] Pop-up Drain

**Architectural/Engineering Approval** 

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.



TAG \_\_\_\_\_

## Rough-in/Overview dimensions

