

### Architectural/Engineering Specification:

Zurn HYDRO-X Power sensor faucets are ideal for high-use applications where **sustainable power**, **durability** and **hands-free operation** are necessary. Self-sustaining hydropower with battery backup for ten years of trouble-free operation, ADA compliant, polished chrome-plated cast brass sensor faucet with infrared proximity sensor for retrofit and new construction. Unit is furnished with a standard 0.5 GPM flow control and mounting hardware.

Zurn Lead Free products (-XL) is the line of durable, high quality brass faucets and fixtures that are designed and manufactured to comply with Section 1417 of the Safe Drinking Water Act (SDWA) which mandates the weighted average lead content of no more than 0.25% of the wetted surface.

### Product Features:

- Self-Sustaining Hydropower for 10+ years operation
- Battery Backup
- Line Purge Mode (adjustable)
- Metering Mode (adjustable)
- 30 second Time Out Feature (adjustable)
- Infrared Convergence-Type Proximity Sensor
- Standard Chrome-plated Cast Brass Body
- In-line filter
- Inlet for 1/2" ball riser

### Suffix Options:

- ADM Above Deck Mixer
- CP4 Cover Plate 4"[102] Centers
- CP8 Cover Plate 8"[203] Centers
- H4 Wrist Blade handle for ADM
- MV Temperature Mixing Valve
- SH Supply Hoses for Mixing Valve
- TMV-1 Thermostatic Mixing Valve for Single Faucets

### Alternate Finishes:

- BN Brushed Nickel

### Compatibility

Soap Dispenser:



Z6956-XL-SD

### Compliance and Certification:

- Low-Lead Compliant
- ADA Compliant
- ASME A112.18.1/CSA B125.1



\*This device is WaterSense labeled when used with the appropriate flow rate and certified for residential and private restrooms.



### Aerator Options:

	Flowrate GPM [LpM]	Vandal Resistant	*WaterSense Labeled	Outlet Type
<b>-E</b>	1.5[5.7]	✓	✓	Aerator
<b>-F</b>	0.5[1.9]	✓		Spray (Standard)
<b>-J</b>	1.5[5.7]	✓	✓	Laminar
<b>-K</b>	1.0[3.8]	✓	✓	Laminar
<b>-L</b>	1.0[3.8]	✓	✓	Aerator
<b>-M</b>	0.35[1.3]	✓		Spray
<b>-N</b>	0.5[1.9]	✓		Laminar

### NOTE:

For hard-wired or plug-in applications, please see:  
Z6956-XL-CV

### Architectural/Engineering Approval

The information contained in this document is subject to change without notice.  
Please contact Zurn for most up to date information.

**TYPICAL Z6956-XL**  
Self Sustaining Battery Powered  
Faucet

Recommended through  
hole diameter to properly  
mount the spout/shank is  
1-1/8" to 1-1/4".

